

## FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: C8 or C6 inlet
- Port: 6xTYPE C port
- Ovp, Ocp, Scp and Over load protection
- GAN TECH, 300W PD Charger, smart
- Efficiency level: VI
- Dimension: 125.0\*125.0\*35.0mm(exclude plug)
- Protocol: TypeC PD2.0/PD3.0/PD3.1/PPS, QC4/QC4+/QC3.0/QC2.0 , FCP, SCP, AFC, Apple2.4 , BC1.2, MTK



## SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

## MODEL LIST:

MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
TX-MU6300D	USB C PORT 1	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,28V5A.PPS:3.3-20V5A	140W	C1+C2 Output: 140W+140W C3+C4 Output: 100W+100W C5+C6 Output: 30W+30W C1+C2+C3+C4+C5+C6 Output: 100W+65W+40W+30W+30W+30W Total: 300W
	USB C PORT 2	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,28V5A.PPS:3.3-20V5A	140W	
	USB C PORT 3	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,PPS:3.3-20V5A	100W	
	USB C PORT 4	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,PPS:3.3-20V5A	100W	
	USB C PORT 5	5V/3A,9V/3A,12V/2.5A,20V/1.5A. (PPS:3.3-11V/2.7A)	30W	
	USB C PORT 6	5V/3A,9V/3A,12V/2.5A,20V/1.5A. (PPS:3.3-11V/2.7A)	30W	
TX-MU6300QD	USB C PORT 1	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,28V5A.PPS:3.3-20V5A	140W	C1+C2 Output: 140W+140W C3+C4 Output: 100W+100W C5+C6 Output: 30W+22W C1+C2+C3+C4+C5+C6 Output: 100W+65W+40W+30W+30W+22W Total: 300W
	USB C PORT 2	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,28V5A.PPS:3.3-20V5A	140W	
	USB C PORT 3	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,PPS:3.3-20V5A	100W	
	USB C PORT 4	PD: 5V3A,9V3A,12V3A,15V3A,20V5A,PPS:3.3-20V5A	100W	
	USB C PORT 5	5V/3A,9V/3A,12V/2.5A,20V/1.5A. (PPS:3.3-11V/2.7A)	30W	
	USB A PORT 6	5V3A,9V2A,12V1.5A,SCP:3.3-11V2A (22W Max)	22W	

## Mechanical Diagram:

